CNYR-48 MS NO. NSN NO. DRAWING NO. NOTES: 1. BUSHING IS IMPREGNATED WITH OIL 2. ALL EXPOSED STEEL SURFACES HAVE BLACK OXIDE ISO VIEW SCALE 1.125 : 1 .9425 .9275 R20 **CROWN** N Ø3/32 LUBE 2X Ø1 3/32 SIDE VIEW SCALE 2.250: 1 ø:4377 4371 SECTION A-A SCALE 2.250 : 1 ZONE HARDENED- $\begin{array}{c} \text{XX} = \pm .01 \\ \text{XXX} = \pm .005 \\ \text{XXXX} = \pm .0005 \\ \text{ANGLES} = \pm 1 \\ \text{INCH [METRIC]} \\ \text{FRACTION} = \pm 1/32 \end{array}$ CARTER MANUFACTURING IS NOT RESPONSIBLE FOR TYPOGRAPHICAL ERRORS CUSTOMER PART# **CARTER MANUFACTURING CO., INC.** MATERIAL NOTES: GRAND HAVEN, MICHIGAN 49417 OUTER RING - BEARING STEEL, HEAT TREATED REVISION PART NAME: ASSEMBLY INNER RING - BEARING STEEL, ZONE HARDENED BUSHING - SINTERED BRONZE ENGINEERING CHANGE ORDER NOTE AUTHOR BY DRAWN BY CHK'D BY SALES MATERIAL Α WASHER(S) - COLD ROLLED STEEL, HEAT TREATED\* MD HG SGW KR NOTED REVISON BY DATE DATE DATE DATE SHEET \*(DEPENDING ON MATERIAL AVAILABILITY, MAY BE CONSTRUCTED FROM BEARING STEEL)

SGW

11/10/2016

11/8/2016

11/9/2016

11/11/2016

1 OF 2