LOAD RATINGS						
RATING	lbf	Newtons				
DYNAMIC LOAD RATING	1,850	8,229				
STATIC THRUST LOAD	480	2,135				
STATIC RADIAL LOAD	780	3,470				

1. BALL BEARINGS COME PRE-PACKED WITH GREASE.


2. THE OUTER RING SHALL BE INSTALLED SO THE O.D. CORNER WITH THE 1/32 X 45° CHAMFER IS ON THE SAME SIDE AS THE INNER RING FLANGE FACE(AS SHOWN).

3. OUTER RING, RETAINING RING GROOVE CONFORMS TO DIN 472. 4. OUTER RING, INNER RING & WASHER: ALL EXPOSED SURFACES

HAVE BLACK OXIDE.

5. CUSTOM LASER ETCHING AVAILABLE UPON REQUEST






DRAWING NO


VHRY-250-A

SIGNED DRAWING APPROVAL REQUIRED

PLEASE REVIEW AND VERIFY INFORMATION ON ALL SHEETS & RETURN COPY WITH SIGNED AND DATED APPROVAL, AND/OR REQUIRED CHANGES. CARTER WILL NOT PROCEED WITH ORDER UNTIL APPROVAL IS RECEIVED

APPROVED REJECTED SIGNED





NSN NO.

MATE	RIAL	NOT	TES:
------	------	-----	------

OUTER ROLLER HOUSING - BEARING STEEL, HEAT TREATED

YOKE - STEEL WASHER - STEEL

BALL BEARING(S) - 6903 2RS (17mm X 30mm x 7mm) RETAINING RING - DHO-30 OR EQUIVALENT

CUSTOMER PART#	TOMER PART# XX = ± .01	CARTER MANUFACTURING IS NOT RESPONSIBLE FOR TYPOGRAPHICAL ERRORS		CARTER MANUFACTURING CO., INC. GRAND HAVEN, MICHIGAN 49417			
	INCH [METRIC] FRACTION = ± 1/32			PART NAME: ASSEMBLY		PRODUCT TY	PRODUCT TYPE: VHRY
ENGINEERING CHANGE ORDER NOTE		В	AUTHOR BY	DRAWN BY	CHK'D BY	SALES	MATERIAL
		В	HG	SGW	MD	NC	NOTED
		REVISON BY	DATE	DATE	DATE	DATE	SHEET
		SGW	3/8/2021	8/22/2018	3/5/2021	3/10/2021	1 OF 2